

Wöhler VIS 350 Visual Inspection Camera

TECHNICAL DATA

Monitor

Dimensions housing.....176 x 114 x 32 mm
 TFT-Display.....7" / 16:9 format
 Video-Out.....RCA signal
 Weight.....400 g

Power Supply.....Space for 2 rechargeable batteries, each 12 V or via power pack
 Battery operating time.....Max. 2 rechargeable batteries, each 120 mins. = 4 h
 (battery status in display)

Pan&tilt Ø 40 mm color camera head

Type.....1/3" COLOR CMOS
 Pixels.....768 x 576 (PAL), 656 x 492 (NTSC)
 Light sensitivity.....0.5 Lux
 Lens.....f = 2.3 mm, F = 2.5
 Viewing angle.....115°
 Light source.....12 white LEDs
 Degree of protection.....Waterproof to IP 67
 Dimensions.....Ø 40 mm x 60 mm
 Operating temperature.....0...40 °C, RH 95 % MAX
 Storage temperature.....-20...50 °C, RH 95 % MAX

Push rod

Length.....20 m
 Diameter.....6.5 mm

Plastic case

Dimensions.....51 x 43 x 17 cm (L x W x H)
 Weight.....8.2 kg

Distance Measurement

Wöhler VIS 350/VIS 300.....Electronic meter counter

Memory (Wöhler VIS 350)

Recording.....2 GB SD card (2.5 h recording capacity)
 Interface.....Mini USB port

Locator transmitter

Transmission frequency.....8.9 kHz

Locator receiver

Display.....Graphic visualization of transmitted position
 Output impedance.....
 Headphones.....32 Ohm
 Power supply.....3.7 V Li-Ion rechargeable battery
 Operating temperature.....0...40 °C
 Storage temperature.....-10 °C...40 °C
 Weight.....605 g
 Dimensions.....32 x 14 x 7 cm (L x W x H)